

HOBBLE CLAMP RANGE*	2-Bolt Double Eye Clamp Number:	2-Bolt Single Eye Clamp Number:	4-Bolt Double Eye Clamp Number:	4-Bolt Single Eye Clamp Number:	APPROX WEIGHT** (LBS)
5/8" - 7/8"	2BDE-075	-	-	-	1.35
7/8" - 1-1/8"	2BDE-100	-	-	-	1.50
1-1/8" - 1-3/8"	2BDE-125	-	-	-	1.60
1-3/8" - 1-5/8"	2BDE-150	-	-	-	1.65
1-45/64" - 2-1/8"	2BDE-196	2BSE-196	-	-	4.05
2-1/8" - 2-1/2"	2BDE-238	-	4BDE-238	-	4.85
2-1/2" - 2-3/4"	2BDE-263	2BSE-263	4BDE-263	-	4.85
2-13/16" - 3-1/4"	2BDE-300	2BSE-300	4BDE-300	-	5.00
3-3/8" - 3-5/8"	2BDE-350	2BSE-350	4BDE-350	-	5.50
3-3/4" - 4-1/8"	2BDE-400	2BSE-400	4BDE-400	-	5.75
4-1/4" - 4-5/8"	2BDE-450	2BSE-450	4BDE-450	4BSE-450	11.00
4-3/4" - 5-1/2"	2BDE-500	2BSE-500	4BDE-500	4BSE-500	12.00
5-5/16" - 5-3/4"	2BDE-550	2BSE-550	4BDE-550	4BSE-550	12.25
5-13/16" - 6-1/4"	2BDE-600	2BSE-600	4BDE-600	4BSE-600	14.35
6-5/16" - 6-3/4"	2BDE-650	2BSE-650	4BDE-650	4BSE-650	15.50
6-7/8" - 7-1/2"	2BDE-725	2BSE-725	4BDE-725	4BSE-725	17.25
7-13/16" - 8-3/4"	2BDE-800	2BSE-800	4BDE-800	4BSE-800	19.00

2BDE = 2 BOLT 4BDE = 4 BOLT DE = DOUBLE EYE SE = SINGLE EYE

***Hose Outside Diameter must fit with clamp range, (do not order solely based on hose ID)**

Shackle sizes: Use 3/8" through size -150, 1/2" with sizes 196 - 450 Single Eye, 3/4" with sizes 196 - 450 Double Eye and for -500 and larger (either single or double eyed versions)

A properly sized clamp should have a gap when installing. If two clamp halves are touching, the clamp cannot seal.

Torque bolts on clamps through 4 inch to 45 Ft Lbs, and 55-60 Ft lbs on clamps 4.5" and larger.

Check and re-tension regularly. Install 12 inches from end of coupling ferrule or hose clamp.

Clamps are made from electrostatic powder coated carbon steel (width & thickness vary by size)

*** Weight is based on 2 bolt double eye hobble clamp. Use only as a rough guide for estimation*